DOI: 10.19812/j.cnki.jfsq11-5956/ts.20241217002

引用格式:顾显显,方燕,刘华良.基于顶空-气相色谱-质谱法的食用油中润滑油挥发性组分快速筛查方法研究[J]. 食品 安全质量检测学报,2025,16(9):99–105.

GU XX, FANG Y, LIU HL. Research on rapid screening method for volatile components of lubricating oil in edible oil based on headspace-gas chromatography-mass spectrometry [J]. Journal of Food Safety & Quality, 2025, 16(9): 99–105. (in Chinese with English abstract).

基于顶空-气相色谱-质谱法的食用油中润滑油挥 发性组分快速筛查方法研究

顾显显1,方燕2,刘华良1*

(1. 江苏省疾病预防控制中心,南京 210009; 2. 南京市鼓楼区疾病预防控制中心,南京 210003)

摘 要:目的 建立顶空-气相色谱-质谱法测定食用油中混入的润滑油挥发性组分的方法。**方法** 直接取 1.0g油样于 10 mL 顶空瓶中加盖密封,在 90 ℃平衡 20 min 的条件下顶空进样进行气相色谱-质谱仪检测,以 4-甲基-2-戊醇、异辛醇、壬烷、十一烷和十二烷 5 种化合物定性,以异辛醇、壬烷、十一烷和十二烷 4 种化 合物定量。结果 4 种定量化合物在 0.5~8.0 mg/kg 范围内线性关系良好,相关系数均大于 0.9980。以大豆油 为加标实验样品,壬烷、异辛醇、十一烷和十二烷的加标回收率分别为 91.5%~98.2%、81.9%~92.7%、 92.8%~94.6%、89.3%~93.7%,相对标准偏差均小于 10%。在大豆油、花生油、菜籽油、玉米油、葵花籽油 5 种食 用油中壬烷、异辛醇、十一烷和十二烷的检出限分别为 0.006~0.013 mg/kg、0.016~0.045 mg/kg、0.011~0.020 mg/kg 和 0.020~0.036 mg/kg。**结论** 该方法具有操作简单、检测快速等优势,对仪器要求不高,一般实验室均能开 展,适用于食用油中微量润滑油污染的筛查。

关键词: 顶空-气相色谱-质谱法; 食用油; 润滑油; 挥发性组分

Research on rapid screening method for volatile components of lubricating oil in edible oil based on headspace-gas chromatography-mass spectrometry

GU Xian-Xian¹, FANG Yan², LIU Hua-Liang^{1*}

Jiangsu Provincial Center for Disease Control and Prevention, Nanjing 210009, China;
 Nanjing Gulou Provincial Center for Disease Control and Prevention, Nanjing 210003, China)

ABSTRACT: Objective To establish a method for determining the volatile components of lubricating oil mixed in edible oil by headspace-gas chromatography-mass spectrometry. **Methods** The 1.0 g oil sample was directly taken into a 10 mL headspace bottle, then capped and sealed. Headspace-gas chromatography-mass spectrometry analysis was carried out at 90 °C equilibration for 20 min. Qualitative analysis was performed on 5 kinds of compounds: 4-methyl-2-pentanol, isooctanol, nonane, undecane and dodecane, while quantitative analysis was performed on

收稿日期: 2024-12-17

第一作者:顾显显(1994—),女,主管技师,主要研究方向为水质及食品检测。E-mail: 1140866141@qq.com

^{*}通信作者: 刘华良(1973—), 男, 研究员, 主要研究方向为卫生理化研究。E-mail: 437971057@qq.com

isooctanol, nonane, undecane, and dodecane. **Results** The 4 kinds of quantitative compounds showed good linear relationships within the range of 0.5–8.0 mg/kg, and the correlation coefficients were all above 0.9980. Soybean oil was used as the sample for the spike recovery experiment. The recoveries of nonane, isooctanol, undecane, dodecane were 91.5%–98.2%, 81.9%–92.7%, 92.8%–94.6%, 89.3%–93.7% respectively and the relative standard deviations were all less than 10%. In the 5 kinds of edible oils: Soybean oil, peanut oil, rapeseed oil, corn oil and sunflower seed oil, the limits of detection of nonane, isooctanol, undecane, dodecane were 0.006–0.013 mg/kg, 0.016–0.045 mg/kg, 0.011–0.020 mg/kg, 0.020–0.036 mg/kg respectively. **Conclusion** This method has the advantages of simple operation and rapid detection, and does not have high requirements for the instrument, which can be carried out in general laboratories, and is suitable for the screening of trace lubricating oil contamination in edible oil.

KEY WORDS: headspace-gas chromatography-mass spectrometry; edible oil; lubricating oil; volatile components

0 引 言

食品安全与社会稳定发展密切相关,当食品安全出 现问题时会威胁公众健康,破坏社会稳定。随着生活水平的 提高,人民对食品安全问题也越发关注。2024年7月"中储 粮油罐车混装食用油"事件也暴露出我国面临的食品安全问 题的严峻性[1-2]。食用油作为日常生活的必需品,保障其质 量安全尤为重要。煤制油是指以煤炭为原料经过各种化学 反应形成多碳化合物,再进行重整、裂化、合成后的矿物 油产品,如柴油、汽油、煤油、润滑油等^[3]。其主要化学 成分是 C10~C50 的烃类化合物,包括直链、支链和烷基取 代的环状饱和烷烃(mineral oil saturated hydrocarbons, MOSH)以及烷基取代的芳香烃(mineral oil aromatic hydrocarbons, MOAH)两类^[4]。欧洲食品安全局(European Food Safety Authority, EFSA)在 2012 年发布的评估报告^[5]中 指出, MOSH 几乎存在于所有食品中。有研究表明, 矿物油 经膳食摄入后易在人体内长期蓄积,是人体内蓄积量最大 的污染物, 而芳香烃类矿物油更是具有致突变性, 含有 3 个以上苯环的芳香烃还有遗传致癌性[6-7]。本研究所涉及的 5种化合物都属于 MOSH。其中 4-甲基-2-戊醇、十一烷、 十二烷因其润滑性、黏度特性和热稳定性,常被用作润滑 油的基础油成分, 广泛应用于多个领域; 而壬烷在润滑油 中主要作为添加剂或溶剂,能调节润滑油的黏度,提升其 性能,使其更适合在低温低黏度条件下使用。异辛醇既可 以做基础油组分也可以充当添加剂及溶剂,能够提升润滑 油的抗氧化、抗腐蚀性能,还能改善润滑油的生物降解, 减少对环境的影响。

氢火焰离子化检测器因其对碳响应完全一致的特点成为矿物油定量测定的首选方法。目前,在线高效液相色谱-气相色谱氢火焰离子化检测器法(high performance liquid chromatography-gas chromatography-hydrogen flame ionization detector, HPLC-GC-FID)和离线固相萃取气相色谱氢火焰离子化检测器法(solid phase extraction-gas

chromatography-hydrogen flame ionization detector. SPE-GC-FID)^[8-13]是最常用的矿物油分析方法。HPLC-GC 通过 HPLC 与 GC 的 Y 接口技术实现在线净化、富集,有 效提高了矿物油的分离和检出限,且干扰较少;而离线 SPE 主要是利用银渍硅胶和氧化铝复合净化柱对样品进行 净化、富集,再配合程序升温气化进样口(programmable temperature vaporizer, PTV)进行分析。此外, 刘亮等^[14]采用 气相色谱-质谱法检测矿物油在肉鸡体内的残留量变化, 但是由于矿物油结构信息不足、没有共同的离子碎片也无 法有效地分别定量 MOSH 和 MOAH; 钱沙沙等^[15]采用全 二维气相色谱法测定食品接触用纸制品中饱和烃矿物油的 迁移量, 全二维气相色谱利用化合物极性和沸点的不同, 进 行二次分离,能够对一维气相色谱无法解决的碳混合物进 行有效地分离和定量[16]。同时有研究表明,在相同分析时 间和条件下,全二维的峰容量可达到一维色谱的10倍^[17]。

但由于 HPLC-GC-FID、SPE-GC-FID 以及全二维气相 色谱法或需配备大体积进样系统或因仪器价格昂贵,普及 率不高,大部分实验室均不具备可行性。故本研究尝试用 常见的顶空-气相色谱-质谱法对食用油中混入的微量润滑 油主要成分进行定性定量分析,作为食用油被润滑油污染 的初步筛查手段。

1 材料与方法

1.1 材料、试剂与仪器

金龙鱼大豆油、鲁花花生油、福临门菜籽油、福临门 玉米油、金龙鱼葵花籽油:均从超市购入;润滑油(太行润 滑煤制油,山西潞安太行润滑科技股份有限公司)。

十一烷(纯度 99.9%)、十二烷(纯度 99.6%)、壬烷(纯 度 99.5%)、正己烷(色谱纯)(上海安谱公司); 异辛醇(纯度 99.0%, 上海阿拉丁公司)。

7890B-5977A 气相色谱质谱仪(配全自动顶空进样器 7697A、10 mL 顶空瓶带聚四氟乙烯瓶盖)、DB-5MS 色谱 柱(30 m×0.25 mm, 0.25 µm)(美国安捷伦公司); MA204 万 分之一天平(瑞士梅特勒-托利多公司)。

1.2 方 法

1.2.1 样品前处理

称取1g(精确至0.01g)样品于10 mL顶空瓶中加盖密 封后水平摇动混匀,待测。待测样品应在洁净环境中室温 保存,取样前要充分混匀样品,取样后要及时密封好样品; 注意样品的有效期和保存期,防止样品酸败变质,影响实 验结果。

1.2.2 标准溶液配制

(1)标准储备液的配制

分别准确称取 0.1000 g 壬烷、异辛醇、十一烷、十二 烷于 4 个 10 mL 容量瓶中,用正己烷定容至刻度,混匀。 得到壬烷、异辛醇、十一烷、十二烷单标储备液质量浓度 均为 10000 mg/L。

(2)混合标准使用液的配制

分别准确吸取 0.1 mL 壬烷、异辛醇、十一烷、十二烷 单标储备液于 10 mL 容量瓶中,用正己烷定容至刻度,混 匀。得到 4 种化合物混合标准使用液质量浓度为 100 mg/L。

(3)纯溶剂标准曲线的配制

准确吸取 1.0 mL 正己烷于 10 mL 顶空瓶中,平行 6 份,分别加入混合标准使用液 0、5、10、20、40、80 μL,加 盖密封,配制成含壬烷、异辛醇、十一烷、十二烷浓度均为 0、0.5、1.0、2.0、4.0、8.0 mg/kg 的纯溶剂标准系列。保持 顶空样品瓶直立,做水平圆周振摇,使其充分混合。振摇过 程中溶剂不能接触到密封垫,若有接触需重新配制。

(4)基质标准工作曲线的配制

称取1 g(精确至 0.01 g)空白基质样品(不含目标物的 食用油样品)于 10 mL 顶空瓶中,平行 6 份,分别加入混合 标准使用液 0、5、10、20、40、80 μL,加盖密封,配制成 含壬烷、异辛醇、十一烷、十二烷浓度均为 0、0.5、1.0、 2.0、4.0、8.0 mg/kg 的基质标准系列。保持顶空样品瓶直 立,做水平圆周振摇,使物质充分混合。振摇过程中食用 油不能接触到密封垫,若有接触需重新配制。

1.2.3 空白样品制备

将大豆油、花生油、菜籽油、玉米油、葵花籽油5种 代表性基质样品在实验室条件下经90℃加热30min并通 入干燥氮气处理^[18],确保本底不含待测目标化合物干扰后 作为空白样品。

1.2.4 仪器条件

(1)气相色谱条件

DB-5MS 色谱柱(30 m×0.25 mm, 0.25 µm); 柱温采用 程序升温: 40 ℃保持 3 min, 以 10 ℃/min 升至 220 ℃保持 1 min; 进样口温度 180 ℃; 分流比 20:1; 载气为高纯氦气, 柱流量为 1.0 mL/min。

(2)质谱条件

电子轰击源(electron impact ionization, EI), 离子源

230 ℃,四极杆 150 ℃,传输线 280 ℃。采集模式:选择离 子模式(selected ion monitor, SIM),溶剂延迟 5 min,增益 因子 1.0,各化合物离子信息见表 1。

表 1 各化合物离子信息 Table 1 Ion information for each compound

146101	1011 11101 11111101 101 1	uun tompounu
化合物	定量离子	定性离子
4-甲基-2-戊醇	/	87,69,45,43
壬烷	57	85,43,41
异辛醇	57	84,70,43
十一烷	57	85,71,43
十二烷	57	85,71,43

注:/表示未做定量分析,只定性。

(3)顶空进样器条件

炉温 90 ℃, 定量环 110 ℃, 传输线 130 ℃; 顶空瓶平 衡 20 min, 加压 1 min, 进样时间 0.5 min。

1.2.5 定性及定量分析

按照上述条件对样品进行测定,根据保留时间定性, 外标法定量。以各目标化合物的浓度为横坐标(*X*, mg/kg), 峰面积为纵坐标(*Y*)绘制基质标准曲线,通过基质标准曲线 来计算样品中各目标化合物的含量。

1.3 数据处理

本研究前处理条件优化均为3次平行样品测定,方法 学验证为6次平行测定。顶空-气相色谱-质谱联用仪测得 的数据通过安捷伦 MassHunter Workstation 工作站进行标 准曲线绘制及线性方程计算。利用 WPS Office Excel 2019 软件对数据进行统计分析和制作表格,采用 Origin 2019b 软件绘图。

2 结果与分析

2.1 目标化合物的确定

选取市面上某润滑油产品以及常用的 5 种食用油(大 豆油、花生油、菜籽油、玉米油、葵花籽油)作为实验对象, 分别称取1g样品于10 mL顶空瓶中,加盖密封,用气相色 谱-质谱仪进行全扫描分析。通过比较润滑油与5 种食用油 的全扫描图谱,选出润滑油中含有而5 种食用油中均不含有 的化合物作为润滑油污染的标志物。本研究选出了壬烷、异 辛醇、十一烷和十二烷4 种可定量的化合物,4-甲基-2-戊醇 则因缺少标准品而作为定性化合物。润滑油中还含有其他一 些化合物,且在 5 种食用油中也未检出,但因其含量较低 不予考虑。其中润滑油和大豆油的全扫描图谱见图1。

2.2 正己烷体积对响应的影响

以大豆油为实验对象,分别称取1g大豆油于6个10mL 顶空瓶,加入50μL质量浓度为100mg/L的混合标准使用液, 再分别加入不同体积的正己烷,加盖密封后水平摇动混匀





进行测定。考察在油样中加入正己烷以增加油样的流动性 和挥发性是否能提高化合物的响应。结果表明(图 2),当1g 试样中正己烷体积大于 80 μL 时,壬烷和十一烷峰面积呈 下降趋势;当正己烷体积达到 500 μL 时,异辛醇和十二烷 峰面积也呈下降趋势。研究结果表明在试样中加入正己烷 并不能增加 4 种化合物的响应,还会降低其峰面积,这可 能是正己烷的大量挥发反而占据了顶空气大部分体积,稀 释了目标化合物的浓度。其产生的负效应大于上层顶空体 积缩小的正效应。故为了实验的准确性在配制工作曲线时 应尽量控制加入的正己烷体积均在 80 μL 以内,否则基质 曲线高浓度点的峰面积就会偏低而影响线性。

2.3 顶空平衡温度与时间的优化

以大豆油为实验对象,取1g大豆油于10mL顶空瓶 中,加入50μL质量浓度为100mg/L的混合标准使用液后 考察不同平衡温度和时间对目标化合物峰面积的影响。先 考察 80 ℃时不同平衡时间(10、20、30、40、50 min)下目标化合物峰面积情况。结果发现随着时间的增加,峰面积增加,20 min 时趋于稳定,40 min 后又有所下降(图 3a)。为了减少检测时间提高效率,故选择 20 min 的平衡时间。再考察 20 min 下不同平衡温度(50、60、70、80、90 ℃)时目标化合物峰面积情况。结果表明,在相同平衡时间下,随着温度增加,目标化合物峰面积随之增加,90 ℃时达到峰值,考虑到方法的灵敏度需要,故选择 90 ℃的平衡温度。其次,从图 3b 中的面积增长趋势来看,温度继续升高各化合物峰面积还会进一步增加,但是考虑到温度过高可能会影响顶空瓶瓶盖的气密性和耐热性,甚至导致更多挥发性物质及热分解产物^[19-20]的干扰,故本研究不再考察更高的顶空温度。4 种目标化合物在不同顶空平衡时间以及平衡温度下的峰面积见图 3。









图 3 4 种目标化合物在不同顶空平衡时间(a)以及平衡温度(b)下的峰面积

Fig.3 Peak areas of 4 kinds of target compounds at different headspace equilibrium times (a) and equilibrium temperatures (b)

第9期

2.4 基质效应考察

目前,在顶空进样的方法学研究中,基质效应(matrix effects, ME)越来越被学者所重视。有相关研究表明,样品 基质的存在及量的变化确实会影响实验的结果^[21-23]。按 1.2.2 分别配制纯溶剂标准曲线和 5 种食用油基质匹配的标 准工作曲线进行测定。根据每种目标化合物在纯溶剂标准 曲线和 5 种食用油基质匹配的标准工作曲线中获得的线性 方程,按公式(1)计算 ME^[24-25]。当 ME<0 时表示基质抑制 效应, ME>0 时表示基质增强效应,其中当 ME 的绝对值为 0%~20%时为弱 ME, 20%~50%时为中等 ME, ME>50%时为 强 ME^[26-29]。

ME/%=
$$(\frac{S_{\rm m}}{S_{\rm s}} - 1) \times 100\%$$
 (1)

式中: S_m和 S_s分别表示基质匹配标准工作曲线和纯溶 剂标准曲线的斜率。

表 2 为 4 种目标化合物在不同食用油样品基质中的

ME 情况。由表 2 可以看出, 壬烷在 5 种食用油中均呈弱 ME, 异辛醇均呈强 ME, 十一烷除在玉米油中均呈中等 ME, 十二烷则在大豆油和玉米油中呈中等 ME, 在另外 3 种食用油中呈强 ME。故异辛醇、十一烷和十二烷在不同 食用油样品中的 ME 是不可忽略的。因此, 在检测工作中 要注意 ME 对于结果的影响, 尤其当测定值处于限值时, 要尽量采取基质配标等方法消除 ME^[30]。

2.5 线性范围、回归方程和检出限

在 0.5~8.0 mg/kg 的线性范围内, 4 种目标化合物在 5 种常用食用油中的回归方程见表 2, 线性关系良好, 相关系数均在 0.9980 以上。以 3 倍信噪比计算, 壬烷在大豆油、花生油、菜籽油、玉米油、葵花籽油中的检出限分别为 0.006、0.010、0.010、0.013、0.010 mg/kg, 异辛醇的检出限分别为 0.045、0.023、0.029、0.016、0.022 mg/kg, 十一烷的检出限分别为 0.045、0.023、0.029、0.016、0.022 mg/kg, 十一烷的检出限分别为 0.013、0.011、0.012、0.013、0.020 mg/kg, 十二烷的检出限分别为 0.025、0.021、0.020、0.028、0.036 mg/kg。

Table 2	ME of 4 kinds of target compounds in different edible oil sample matrices
	表 2 4 种目标化合物在不同食用油样品基质中的 ME

目标化合物名称	基质	回归方程	相关系数(r)	斜率	ME/%
壬烷	溶剂	<i>Y</i> =16520 <i>X</i> -1493	0.9996	<i>S</i> _s : 16520	/
	大豆油	<i>Y</i> =16910 <i>X</i> -1604	0.9983	<i>S</i> _m : 16910	2.4
	花生油	<i>Y</i> =15110 <i>X</i> +723	0.9981	<i>S</i> _m : 15110	-8.5
	菜籽油	<i>Y</i> =14790 <i>X</i> +3707	0.9993	<i>S</i> _m : 14790	-11.0
	玉米油	<i>Y</i> =17450 <i>X</i> +81	0.9990	<i>S</i> _m : 17450	5.6
	葵花籽油	<i>Y</i> =16880 <i>X</i> -810	0.9995	<i>S</i> _m : 16880	2.2
异辛醇	溶剂	<i>Y</i> =3304 <i>X</i> -839	0.9991	<i>S</i> _s : 3304	/
	大豆油	<i>Y</i> =1154 <i>X</i> -347	0.9982	<i>S</i> _m : 1154	-65.0
	花生油	<i>Y</i> =940 <i>X</i> +252	0.9985	<i>S</i> _m : 940	-72.0
	菜籽油	<i>Y</i> =911 <i>X</i> +221	0.9994	<i>S</i> _m : 911	-72.0
	玉米油	<i>Y</i> =1161 <i>X</i> -214	0.9993	<i>S</i> _m : 1161	-65.0
	葵花籽油	<i>Y</i> =1004 <i>X</i> -172	0.9996	<i>S</i> _m : 1004	-70.0
	溶剂	<i>Y</i> =6794 <i>X</i> -1796	0.9993	<i>S</i> _s : 6794	/
	大豆油	<i>Y</i> =5102 <i>X</i> -1993	0.9982	S _m : 5102	-25.0
十二/信	花生油	<i>Y</i> =3922 <i>X</i> +544	0.9981	<i>S</i> _m : 3922	-42.0
一元	菜籽油	<i>Y</i> =3993 <i>X</i> +596	0.9991	<i>S</i> _m : 3993	-41.0
	玉米油	<i>Y</i> =5736 <i>X</i> -1495	0.9990	<i>S</i> _m : 5736	-16.0
	葵花籽油	<i>Y</i> =4842 <i>X</i> -1115	0.9994	<i>S</i> _m : 4842	-29.0
十二烷	溶剂	<i>Y</i> =4453 <i>X</i> -1564	0.9992	<i>S</i> _s : 4453	/
	大豆油	<i>Y</i> =2430 <i>X</i> -1011	0.9984	<i>S</i> _m : 2430	-45.0
	花生油	<u>Y=1715X+411</u>	0.9988	<i>S</i> _m : 1715	-61.0
	菜籽油	Y=1666X+442	0.9992	<i>S</i> _m : 1666	-63.0
	玉米油	Y=2653X-737	0.9994	<i>S</i> _m : 2653	-40.0
	葵花籽油	<u>Y=2025X-359</u>	0.9991	<i>S</i> _m : 2025	-55.0

注:/表示溶剂本身不参与 ME 的计算。

2.6 回收率和精密度

根据上述样品处理方法,选取大豆油作为样品进行加标回收实验,加标浓度为1.0、2.0、5.0 mg/kg,每个浓度水平 6 个平行,结果见表 3。在低、中、高 3 个加标浓度水平下 4 种化合物的回收率范围在 81.9%~98.2%, RSDs 范围在 2.1%~8.3%,均符合检测要求。

	1	arget compounds in soybean oil samples (<i>n</i> =6)
Table	3	Results of spiking recovery experiments for 4 kinds of
表 3	4 秆	▶目标化合物在大豆油样品中的加标回收实验结果(n=6)

化合物	本底值 /(mg/kg)	加标值 /(mg/kg)	测得值 /(mg/kg)	平均 回收率/%	RSDs/%
壬烷	/	1.0	0.915	91.5	5.0
	/	2.0	1.964	98.2	2.1
	/	5.0	4.821	96.3	6.9
异辛醇	/	1.0	0.927	92.7	8.3
	/	2.0	1.638	81.9	6.8
	/	5.0	4.483	89.7	6.1
十一烷	/	1.0	0.938	93.8	5.0
	/	2.0	1.892	94.6	4.1
	/	5.0	4.640	92.8	6.3
十二烷	/	1.0	0.937	93.7	6.9
	/	2.0	1.786	89.3	6.4
	/	5.0	4.505	90.1	7.1

注: /表示未检出; 相对标准偏差(relative standard deviation, RSD)。

2.7 实际食用油样品的检测

根据上述样品处理方法,对从超市购入的金龙鱼大 豆油、鲁花花生油、福临门菜籽油、福临门玉米油、金龙 鱼葵花籽油 5 种日常食用油样品进行检测。结果显示 5 种 食用油样品中均未检出 4-甲基-2-戊醇、异辛醇、壬烷、十 一烷和十二烷。

3 结 论

本研究采用顶空-气相色谱-质谱法对食用油中混入的 润滑油主要成分进行定性定量分析,作为润滑油污染的初 步筛查手段。方法较在线 HPLC-GC-FID、离线 SPE-GC-FID 和二维气相更为简单快捷,对仪器要求不高,一般实验室 均能开展。在大豆油、花生油、菜籽油、玉米油、葵花籽 油 5 种食用油中可定量的壬烷、异辛醇、十一烷和十二烷 检出限分别为 0.006~0.013 mg/kg、0.016~0.045 mg/kg、 0.011~0.020 mg/kg 和 0.020~0.036 mg/kg,均低于 0.1 ppm。 对于 30 t 的油罐车来说,混入 3 L 润滑油就能被本方法检 测到,足够满足食用油中微量润滑油的污染筛查,同时其 加标回收率和精密度均能满足要求。不足的是,本研究仅 选取了某润滑油产品中的 5 种化合物作为润滑油污染标志 物,可能存在一定的局限性,需进一步扩大润滑油污染标 志物的组分范围,以便为后续研究提供改进方向。

参考文献

 [1] 裘胜. 常态化疫情防控时期的食品安全问题及对策[J]. 食品安全质量 检测学报,2021,12(15):6228-6232.

QIU S. Food safety issues and countermeasures during the period of normalized epidemic prevention and control [J]. Journal of Food Safety & Quality, 2021, 12(15): 6228–6232.

 [2] 武晓娟. 我国食品安全问题分析及对策研究[J]. 食品科技, 2021(32): 183-185.

WU XJ. Analysis and countermeasures of food safety problems in China [J]. Food Science and Technology, 2021(32): 183–185.

[3] 田丽蓉. 润滑油的化学原理及其应用[J]. 化学工程与装备, 2023, 5(18): 203-204, 209.

TIAN LR. The chemical principle of coal liquefaction and application [J]. Chemical Engineering and Equipment, 2023, 5(18): 203–204, 209.

- [4] 黄湘鹭,邢书霞,罗飞亚,等. 化妆品中矿物油毒理学及其风险评估研究进展[J]. 日用化学工业, 2020, 50(7): 488–495.
 HUANG XL, XING SX, LUO FY, *et al.* Research progress on toxicology and risk assessment of mineral oil in cosmetics [J]. China Surfactant Detergent & Cosmetics, 2020, 50(7): 488–495.
- [5] 钟怀宁,朱蕾,卢倩,等. 食品接触材料中烃类矿物油毒性和风险 管理[J]. 中国卫生检验杂志, 2019, 31(3): 284–290. ZHONG HN, ZHU L, LU Q, *et al.* Toxicology and risk management of the mineral oil hydrocarbons of food contact material [J]. Chinese Journal of Food Hygiene, 2019, 31(3): 284–290.
- [6] 郑建国,陈燕芬,钟怀宁,等. 食品及食品接触材料中烃类矿物油分析 技术进展[J]. 分析测试学报, 2019, 38(11): 1393–1399.
 ZHENG JG, CHEN YF, ZHONG HN, *et al.* Advances in analysis techniques for mineral oil hydrocarbons in foods and food contact materials [J]. Journal of Instrumental Analysis, 2019, 38(11): 1393–1399.
- [7] CARRILLO JC, KAMELIA L, ROMANUKA J, et al. Comparison of PAC and MOAH for understanding the carcinogenic and developmental toxicity potential of mineral oils [J]. Regulatory Toxicology and Pharmacology, 2022, 132: 105–193.
- [8] 杨春艳,张九魁,柯润辉,等. SPE-PTV-GC-FID 法定量分析食用植物 油中的饱和烃类矿物油[J]. 中国食品添加剂, 2018(1): 165–174. YANG CY, ZHANG JK, KE RH, et al. Quantitative analysis of mineral oil saturated hydrocarbons (MOSH) in edible vegetable oils by solid phase extraction-programmed temperature vaporizer-gas chromatography-flame ionization detection (SPE-LVI-GC-FID) method [J]. China Food Additives, 2018(1): 165–174.
- [9] 李冰宁,刘玲玲,武彦文.固相萃取-程序升温-气相色谱法与大容量固相萃取-气相色谱法测定食用油脂中饱和烃矿物油的比较[J].分析试验室,2018,37(6):713-717.

LI BN, LIU LL, WU YW. Comparison of solid phase extraction-programmed temperature vaporizer gas-chromatography and large scale-solid phase extraction-gas chromatography for the determination of mineral oil saturated hydrocarbons in edible oils and fats [J]. Chinese Journal of Analysis Laboratory, 2018, 37(6): 713–717.

[10] 刘玲玲, 武彦文, 李冰宁, 等. 固相萃取-大体积进样-气相色谱法定量 分析油茶籽油中的矿物油[J]. 分析化学, 2016, 44(9): 1419–1424.
LIU LL, WU YW, LI BN, *et al.* Solid phase extraction-large volume injection -gas chromatography method for quantitative analysis of mineral oil in tea seed oil [J]. Chinese Journal of Analytical Chemistry, 2016, 44(9): 1419-1424.

第9期

- [11] 柯润辉,杨春艳,胡雪,等.固相萃取-气相色谱法定量分析橄榄油中 饱和烃矿物油和芳香烃矿物油[J]. 分析化学, 2018, 46(10): 1677–1684. KE RH, YANG CY, HU X, et al. Quantitative analysis of saturated hydrocarbon mineral oil and aromatic hydrocarbon mineral oil in olive oil by solid phase extraction-gas chromatography [J]. Chinese Journal of Analytical Chemistry, 2018, 46(10): 1677–1684.
- [12] 李冰宁,刘玲玲,张贞霞,等.银离子固相萃取-程序升温大体积进样-气相色谱法定量分析市售巧克力中的饱和烷烃矿物油[J].分析化学, 2017,45(4):514-520.

LI BN, LIU LL, ZHANG ZX, *et al.* Quantitative analysis of saturated alkane mineral oils in commercial chocolate using silver ion solid phase extraction-programmed temperature large volume injection-gas chromatography [J]. Chinese Journal of Analytical Chemistry, 2017, 45(4): 514–520.

[13] 简朴. 食用油脂中矿物油污染物的高灵敏检测方法的建立与应用[D]. 北京:北京林业大学, 2022.

JIAN P. Establishment and application of highly sensitive methods for the determination of mineral oil hydrocarbon contaminants in edible oils and fats [D]. Beijing: Beijing Forestry University, 2022.

- [14] 刘亮, 唐善虎, 陈诺, 等. GC-MS 法研究矿物油在肉鸡体内残留动态 变化[J]. 食品科学, 2010, 31(19): 87-91.
 LIU L, TANG SH, CHEN N, *et al.* GC-MS investigation of dynamic changes of mineral oil components in broilers [J]. Food Science, 2010, 31(19): 87-91.
- [15] 钱沙沙,杨洋,张玉萍,等.固相萃取-气相色谱法和全二维气相色谱 法测定食品接触用纸制品中饱和烃矿物油的迁移量[J].食品科学, 2019.40(20):305-310.

QIAN SS, YANG Y, ZHANG YP, *et al.* Comparative determination of migration of mineral oil saturated hydrocarbons from food contact paper-based products by solid phase extraction-gas chromatography and comprehensive two-dimensional gas chromatography [J]. Food Science, 2019, 40(20): 305–310.

- [16] 马媛媛, 蒋启贵, 宋晓莹, 等. 原油中的石油酸组分全二维气相色谱/ 飞行时间质谱分析[J]. 石油实验地质, 2016, 38(5): 685-691.
 MA YY, JIANG QG, SONG XY, *et al.* Analysis of organic acids in crude oil by comprehensive two-dimensional gas chromatography and time-of-flight mass spectrometry [J]. Petroleum Geology and Experiment, 2016, 38(5): 685-691.
- [17] KLEE MS, COCHRAN J, MERRICK M, et al. Evaluation of conditions of comprehensive two-dimensional gas chromatography that yield a near theoretical maximum in peak capacity gain [J]. Journal of Chromatography A, 2015, 1383: 151–159.
- [18] 王宇,韩伟,崔伟佳,等.顶空-气相色谱-质谱法测定食用植物油中苯 残留量[J]. 食品安全质量检测学报, 2020, 11(16): 5688–5694.
 WANG Y, HAN W, CUI WJ, *et al.* Determination of benzene residual in edible vegetable oils by headspace gas chromatography-mass spectrometry [J]. Journal of Food Safety & Quality, 2020, 11(16): 5688–5694.
- [19] 邵华. 静态顶空-气相色谱法测定食品包装用铝箔纸中的苯系物[J]. 江 苏预防医学, 2022, 33(5): 603-604, 618.
 SHAO H. Determination of benzene compounds in aluminum foil paper for food packaging by static headspace-gas chromatography [J]. Jiangsu Journal of Preventive Medicine, 2022, 33(5): 603-604, 618.
- [20] 李天雨,李井涛,王潇.顶空-气相色谱法测定食用油中苯和正己烷的 残留量[J].中国油脂,2017,42(11):113–115.
 LI TY, LI JT, WANG X. Determination of residual amounts of benzene

If I'_{1} , I'_{1} , I

Oils and Fats, 2017, 42(11): 113-115.

- [21] 秦立,胡昌勤,刘文英.顶空气相色谱法测定药品中残留溶剂的影响 因素考察[J].药物分析杂志,2005,25(7):823-826.
 QING L, HU CQ, LIU WY. Investigation of factors affecting the determination of residual solvents in drugs by headspace gas chromatography [J]. Chinese Journal of Pharmaceutical Analysis, 2005, 25(7): 823-826.
- [22] 贺利民,刘祥国,曾振灵. 气相色谱分析农药残留的基质效应及其解决方法[J]. 色谱, 2008, 26(1): 98–104.
 HE LM, LIU XG, ZENG ZL. Solutions to matrix-induced response enhancement in pesticide residue analysis by gas chromatography [J]. Chinese Journal of Chromatograph, 2008, 26(1): 98–104.
- [23] 段醒妹,张晔. 基质效应及其消除[J]. 赤峰学院学报(自然科学版), 2008(8): 17-18.

DUAN XM, ZHANG Y. Matrix effect and its elimination [J]. Journal of Chifeng University (Natural Science Edition), 2008(8): 17–18.

- [24] 马明,周宇艳,赵洁,等.基质匹配顶空-气相色谱法测定纺织品中 DMF, DMAC 与 NMP[J]. 分析试验室, 2015, 34(3): 336–339.
 MA M, ZHOU YY, ZHAO J, *et al.* Determination of DMF, DMAC and NMP in textiles by matrix-matched headspace-gas chromatography [J]. Chinese Journal of Analysis Laboratory, 2015, 34(3): 336–339.
- [25] 张圆圆,刘磊,李娜,等.农药残留检测中不同蔬菜的基质效应[J].农 药学学报,2019,21(3):327-337.
 ZHANG YY, LIU L, LI N, *et al.* Matrix effects in pesticide residue analysis in various vegetable samples [J]. Chinese Journal of Pesticide Science, 2019, 21(3): 327-337.
- [26] 陈杰,王桂泉,胡惠茗. 气相色谱法测定柑橘中农药的基质效应研究[J]. 中国果菜, 2023, 43(6): 49–55. CHEN J, WANG GQ, HU HM. Study on matrix effect of gas chromatography in determination of pesticides in citrus [J]. Chinese Fruit and Vegetable, 2023, 43(6): 49–55.
- [27] 许晓敏,李凌云,林桓,等.基质效应对液相色谱串联质谱分析农药残留的影响研究[J]. 农产品质量与安全, 2019(6): 11–15. XU XM, LI LY, LIN H, *et al.* Study on the impact of matrix effects on the analysis of pesticide residues by liquid chromatography tandem mass spectrometry [J]. Quality and Safety of Agro-Products, 2019(6): 11–15.
- [28] 史俊文,施咏凤,刘华良. Captiva EMR-Lipid 技术结合超高效液相色 谱-串联质谱法测定猪肉中的 17 种磺胺类药物残留[J]. 江苏预防医学, 2023, 34(5): 569–571, 604.
 SHI JW, SHI YF, LIU HL. Determination of 17 sulfonamide residues in

pork by Captiva EMR-Lipid technology combined with ultra-high performance liquid chromatography mass spectrometry [J]. Jiangsu Journal of Preventive Medicine, 2023, 34(5): 569–571, 604.

[29] 何春慧, 邱小元, 钟雪娥, 等. 超高效液相色谱-串联质谱法评价果蔬 中 77 种农药的基质效应[J]. 食品安全质量检测学报, 2024, 15(23): 182–191.

HE CH, QIU XY, ZHONG XE, *et al.* Evaluation of matrix effects of 77 kinds of pesticides in fruits and vegetables by ultra performance liquid chromatography-tandem mass spectrometry [J]. Journal of Food Safety & Quality, 2024, 15(23): 182–191.

[30] 付金贝,沈新春,周婉茹,等. 基于食品用塑料复合膜袋中溶剂残留的基质效应分析研究[J]. 塑料科技,2023,51(6): 59-64.
 FU JB, SHEN XC, ZHOU WR, *et al.* Matrix effect analysis based on solvent residue in plastic composite film bags for food [J]. Plastics Science and Technology, 2023, 51(6): 59-64.

(责任编辑: 安香玉 蔡世佳)